

PERFORMANCE TABLE (4P/60Hz)

| Model (Discharge Bore in mm) | Motor HP | Pole & Hz | Suction air volume at standard condition (Qs in m ³ /min) , required power (La in kW) , pressure (mmAq) | | | | | | | | | | | |
|------------------------------------|-------------|-----------------|--|------|-----------|------|-----------|------|-----------|-------|-----------|-------|-----------|-------|
| | | | 1000 mmAq | | 2000 mmAq | | 3000 mmAq | | 4000 mmAq | | 5000 mmAq | | 6000 mmAq | |
| | | | Qs | La | Qs | La | Qs | La | Qs | La | Qs | La | Qs | La |
| GTW-040 | 2 | 4P/60Hz | 1.74 | 0.89 | 1.58 | 1.24 | | | | | | | | |
| | 3 | 4P/60Hz | 1.74 | 0.89 | 1.58 | 1.24 | 1.45 | 1.59 | 1.35 | 1.93 | | | | |
| | 5 | 4P/60Hz | 1.74 | 0.89 | 1.58 | 1.24 | 1.45 | 1.59 | 1.35 | 1.93 | 1.26 | 2.28 | 1.17 | 2.63 |
| GTW-050 | 2 | 4P/60Hz | 2.17 | 0.98 | | | | | | | | | | |
| | 3 | 4P/60Hz | 2.17 | 0.98 | 1.97 | 1.41 | 1.82 | 1.85 | | | | | | |
| | 5 | 4P/60Hz | 2.17 | 0.98 | 1.97 | 1.41 | 1.82 | 1.85 | 1.69 | 2.28 | 1.57 | 2.72 | 1.47 | 3.15 |
| GTW-065A | 3 | 4P/60Hz | 2.96 | 1.13 | 2.68 | 1.73 | | | | | | | | |
| | 5 | 4P/60Hz | 2.96 | 1.13 | 2.68 | 1.73 | 2.47 | 2.32 | 2.29 | 2.91 | | | | |
| GTW-065B | 3 | 4P/60Hz | 4.59 | 1.63 | | | | | | | | | | |
| | 5 | 4P/60Hz | 4.59 | 1.63 | 4.28 | 2.51 | | | | | | | | |
| | 7.5 | 4P/60Hz | 4.59 | 1.63 | 4.28 | 2.51 | 4.04 | 3.38 | 3.83 | 4.26 | | | | |
| | 10 | 4P/60Hz | 4.59 | 1.63 | 4.28 | 2.51 | 4.04 | 3.38 | 3.83 | 4.26 | 3.65 | 5.13 | 3.49 | 6.01 |
| GTW-080 | 5 | 4P/60Hz | 6.07 | 1.91 | 5.66 | 3.07 | | | | | | | | |
| | 7.5 | 4P/60Hz | 6.07 | 1.91 | 5.66 | 3.07 | 5.34 | 4.23 | | | | | | |
| | 10 | 4P/60Hz | 6.07 | 1.91 | 5.66 | 3.07 | 5.34 | 4.23 | 5.07 | 5.39 | 4.83 | 6.54 | | |
| | 15 | 4P/60Hz | 6.07 | 1.91 | 5.66 | 3.07 | 5.34 | 4.23 | 5.07 | 5.39 | 4.83 | 6.54 | 4.62 | 7.70 |
| GTW-100 | 5 | 4P/60Hz | 7.55 | 2.20 | | | | | | | | | | |
| | 7.5 | 4P/60Hz | 7.55 | 2.20 | 7.03 | 3.64 | | | | | | | | |
| | 10 | 4P/60Hz | 7.55 | 2.20 | 7.03 | 3.64 | 6.64 | 5.07 | 6.30 | 6.51 | | | | |
| | 15 | 4P/60Hz | 7.55 | 2.20 | 7.03 | 3.64 | 6.64 | 5.07 | 6.30 | 6.51 | 6.01 | 7.95 | 5.74 | 9.39 |
| GTW-125 | 7.5 | 4P/60Hz | 11.83 | 3.54 | | | | | | | | | | |
| | 10 | 4P/60Hz | 11.83 | 3.54 | 11.21 | 5.72 | | | | | | | | |
| | 15 | 4P/60Hz | 11.83 | 3.54 | 11.21 | 5.72 | 10.73 | 7.91 | | | | | | |
| | 20 | 4P/60Hz | 11.83 | 3.54 | 11.21 | 5.72 | 10.73 | 7.91 | 10.32 | 10.09 | 9.97 | 12.27 | | |
| | 25 | 4P/60Hz | 11.83 | 3.54 | 11.21 | 5.72 | 10.73 | 7.91 | 10.32 | 10.09 | 9.97 | 12.27 | 9.65 | 14.45 |
| GTW-125A | 7.5 | 4P/60Hz | 14.03 | 3.95 | | | | | | | | | | |
| | 10 | 4P/60Hz | 14.03 | 3.95 | 13.29 | 6.53 | | | | | | | | |
| | 15 | 4P/60Hz | 14.03 | 3.95 | 13.29 | 6.53 | 12.72 | 9.12 | | | | | | |
| | 20 | 4P/60Hz | 14.03 | 3.95 | 13.29 | 6.53 | 12.72 | 9.12 | 12.24 | 11.70 | | | | |
| | 25 | 4P/60Hz | 14.03 | 3.95 | 13.29 | 6.53 | 12.72 | 9.12 | 12.24 | 11.70 | 11.82 | 14.29 | | |

| | | | |
|----------|---|-----|----|
| 馬達顏色(HP) | 2 | 7.5 | 20 |
| | 3 | 10 | 25 |
| | 5 | 15 | |